

# FEED THE OX.

THE GRAVITY WAGON BELT CONVEYOR IS HUNGRY.



*Shown with optional 3-piece telescoping spout*



The Gravity Wagon Belt Conveyor can fill a three-bushel planter box in 12 seconds with 875 BPH at 400 FPM belt speed. Its six-inch conveyor tube and nine-inch cleated belting give you a positive flow. And since its transfer hopper fits many wagons and seed transports, this Ox is ready to get to work if you are.



# GRAVITY WAGON BELT CONVEYOR

## STANDARD FEATURES

- Universal hopper fits many gravity wagons and seed transports.
- Simple operation: pull the rope to start the auger and release to stop.
- Easy installation and removal.
- Conveyor swings left to right and raises/lowers for ease of use.
- Cleated belting - very effective for conveying seed. (The cleat pattern minimizes "fall back").
- Control valve - a spring loaded shut-off with remote rope control for start/stop operation from the discharge end.



SPOUT



TRANSFER HOPPER



CLEATED BELTING



CONTROL VALVE

## SPECIFICATIONS

Capacities	875 BPH at 400 FPM belt speed*. Fills a 3 bushel planter box in 12 seconds.
Conveyor Lengths	6" conveyors available in 16' and 18' lengths.
Conveyor Tube	Galvanized welded tube. Galvanized wind skirt for belting return.
Cleated Belting	9" cleated PVC belt (patented). 1" cleats on 6" centers. Lagged top pulley.
Conveyor Drive	Char-Lynn 6.2 CID hydraulic motor; control valve with remote rope control for discharge end operation, and spring loaded shut-off.
Transfer Boot	Several sizes to fit many gravity wagons and seed transports. Designed for easy installation and removal.

\*400 FPM is the seed industry recommended maximum belt speed.

## OPTIONAL FEATURES

- Solenoid valve control  
*Remote auger operation.  
Eliminates constant rope tension  
required for auger operation.*
- Hydraulic Power kit  
*8 HP gas engine.  
9 GPM hydraulic  
pump. Manual or  
electric start.*
- 4' urethane  
spout
- Three-piece  
telescoping spout (to 15½')



# THERE'S WORK TO DO.

Sudenga Industries • Box 8 • 2002 Kingbird Ave. • George, IA 51237 USA  
1-888-SUDENGA (783-3642) • Fax: 1-712-475-3320 • sales@sudenga.com • www.sudenga.com